WTA Product Testing

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N. 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O. Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

CLIENT : SHANN AUSTRALIA

FACTORY 2 23 BELL STREET PRESTON VIC 3072 TEST NUMBER ISSUE DATE PRINT DATE

: 7-576894-BV : 04/02/2011 : 24/02/2011

SAMPLE DESCRIPTION Clients Ref: "Tentroof"

Woven coated fabric

Colour: White Approx thickness: 1mm

Width: 250cm

End Use: Tents

THESE RESULTS MUST BE CONSIDERED IN CONJUNCTION WITH THE COMMENTS ON THE FOLLOWING PAGE(S)

Material Specification provided by client:

Nominal composition: 100% Polyester

Nominal mass: 800g/m2

Simultaneous determination of Ignitability, Flame AS/NZS 1530.3 - 1999

Propagation, Heat Release and Smoke Release

RESULTS: Face tested: Face

Date tested: 03/02/2011

Mean Standard Error 4.36 36.8 Ignition time min 0.47 Flame propagation time 8.6 S 127.9 Heat release integral kJ/m2 5.0 Smoke release, log d 0.2118 0.221

/m

Optical density, d 1.6395

Number of specimens ignited: 6

Number of specimens tested: 6

REGULATORY INDICES: Ignitability Index 16 Range 0-20

Spread of Flame Index Range 0-10 Heat Evolved Index 8 Range 0-10 Smoke Developed Index 8 Range 0-10

185828 PAGE 1 CONTINUED NEXT PAGE

© Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



This Laboratory is accredited by the National Association of Testing Authorities, Australia, for:
-Chemical Testing of Textiles & Related Products : Accreditation No. 983
-Mechanical Testing of Textiles & Related Products : Accreditation No. 985
-Heat & Temperature Measurement : Accreditation No. 1356

This document is issued in accordance with NATA's accreditation requirements. Samples, and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if ammended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved in advance by the Managing Director of AWTA Ltd.

HAEL A. JACKSON B.Sc.(Hons)

LIMITEE

AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N. 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O. Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

CLIENT : SHANN AUSTRALIA

FACTORY 2 23 BELL STREET PRESTON VIC 3072 TEST NUMBER : 7-576894-BV ISSUE DATE : 04/02/2011 PRINT DATE : 24/02/2011

Comments:

These results only apply to the specimen mounted, as described in this report.

The results of this fire test may be used to directly assess fire hazard, but it should be recognized that a single test method will not provide a full assessment of fire hazard under all fire conditions.

The reaction of thin unsupported flexible materials to flame impingement can be assessed in accordance with AS 1530.2. Where materials of thickness less than 2mm that are sufficiently flexible to be bent by hand around a mandrel of 2mm diameter or less are subjected to the test described herein, they should also be subjected to the test in AS 1530.2.

The specimens were mounted to simulate use in an unsupported or free hanging mode. The results may be significantly different when mounted to simulate a wall cladding or upholstery application.

To allow free movement of sample during testing all corners were folded away from the clamps.

Each test specimen was sandwiched between two layers of galvanised welded square mesh made from wire of nominal diameter $0.8 \, \mathrm{mm}$ and nominal spacing of $12 \, \mathrm{mm}$ in both directions, stapled through at four points, each $100 \, \mathrm{mm}$ from the centre of the sample and the assembly clamped in four places.

 $185828 \hspace{1.5cm} 1 \hspace{1.5cm} (\hspace{1.5cm} \mathtt{END} \hspace{1.5cm} \mathtt{OF} \hspace{1.5cm} \mathtt{REPORT} \hspace{1.5cm}) \hspace{1.5cm} \mathtt{PAGE} \hspace{1.5cm} \hspace{1.5cm} 2$

© Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



This Laboratory is accredited by the National Association of Testing Authorities, Australia, for:
-Chemical Testing of Textiles & Related Products : Accreditation No. 983
-Mechanical Testing of Textiles & Related Products : Accreditation No. 985
-Heat & Temperature Measurement : Accreditation No. 1356

This document is issued in accordance with NATA's accreditation requirements. Samples, and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if ammended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved in advance by the Managing Director of AWTA Ltd.

MICHAEL A. JACKSON B.Sc.(Hons)

MANAGING DIRECTOR

LIMITED