

MARBLE 9 DESIGNER COLORS

Thickness	Hide type	Average size
0.9 – 1.1 mm	Bovine	4.5-5 sqmt (48-55 sqft)

<i>Water and stain repellent already dyed into leather</i>
HIGH TRAFFIC AREA FRIENDLY
RESIDENTIAL – CONTRACT – HOSPITALITY – FASHION

TECHNICAL SPECIFICATIONS

Test	Test method	Mesurment unit	Resoult
Tear strenght-Single edge tear	UNI EN ISO 3377-1	N	➤ = 20
Colour fastness to and from rubbing dry 800 cycles	UNI EN ISO 11640:1998		➤ = 4
Colour fastness to and from rubbing wet 150 cycles	UNI EN ISO 11640:1998		➤ = 3/4
Colour fastness to artificial light Xenon arc	UNI EN ISO 105 B02	Blue scale	➤ = 7
Burning behaviour to cigarette and match flame	BS 5852:1979 BS EN 1021-1-2-:2006		Pass
	NFPA 260		Pass
	CAL TB 170		Pass
Finish adhesion	UNI EN ISO 11644	N/Cm	➤ = 5
Flexing endurance	UNI EN ISO 5402	Cycles	➤ 30.000

The test results are referred only to the sample tested

THE PRODUCT COMPLIES WITH THE **REACH** REGULATION

**LEATHER
MADE IN ITALY**